

# MATERIAL SAFETY DATA SHEET

## EPOXY MORTAR UA - PACK A

### SECTION 1. Identification of the substance/mixture and of the company/undertaking.

- 1.1 Product identifier : Epoxy Products Epoxy Mortar UA - Pack A  
1.2 Relevant identified uses of the substance or mixture and uses advised against  
Use of the substance/mixture : Epoxy resin mortar  
1.3 Details of the supplier of the safety data sheet : Epoxy Products Limited, Unit 7 Haviland Road, Ferndown Industrial Estate,  
Wimborne, Dorset. BH21 7RZ England  
Tel No. +44 (0) 1202 891899  
Email Address – Technical Information : [sales@epoxyproducts.co.uk](mailto:sales@epoxyproducts.co.uk)  
Telephone : +44 (0) 1202 891899  
1.4 Emergency telephone number : +44 (0) 1202 891899

### SECTION 2. Hazards Identification

- 2.1 Classification of the substance or mixture  
Classification according to Regulation 1272/2008 (CLP)  
Skin corrosion/irritant - Category 2 H315 : Causes skin irritation.  
Eye damage/irritant – Category 2 H319 : Causes serious eye irritation  
Skin sensitisation - Category 1 H317 : May cause an allergic skin reaction.  
Aquatic Chronic - Category 2 H411 : Toxic to aquatic life with long lasting effects.

#### 2.2 Label Elements

Hazard pictograms/symbols



Signal Word: Warning

Hazard Statements:

H319: Causes serious eye irritation.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

Precautionary Statements:

- Prevention : Wear protective gloves  
Wear eye or face protection  
Avoid release to the environment  
Response : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Disposal : Disposal of contents/container to be specified in accordance with national regulations.

#### 2.3 Other Hazards

Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annexe X111

Not Applicable

Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annexe X111

Not Applicable

### SECTION 3. Composition/Information on Ingredients

Substance/Mixture	: Mixture				
Component	EINECS	CAS Number	Concentration %	Classification (CLP)	REACH REG
Epoxy Resin Bisphenol Type A	500-033-5	25068-38-6	<20	Skin Corr/Irrit. 2; H315 Eye Dam/Irrit. 2 ; H319 Skin Sens. 1 ; H317 Aquatic Chronic 2, H411	01-2119456619-26
Oxirane, mono{(C12-C14-alkyloxy) methyl} derivs.	271-846-8	68609-97-2	<10	Skin Corr/Irrit. 2; H315 Skin Sens. 1 ; H317	01-2119485289

### 4. First-aid measures

#### 4.1 Description of first aid measures

- Eye Contact : Rinse immediately with plenty of water also under the eyelids for at least 10 minutes. Remove contact lenses. Get medical attention.
- Skin Contact : Wash off immediately with plenty of water for at least 10 minutes. Wash off with soap and water. Immediately remove contaminated clothing and any extraneous chemical without delay.
- Ingestion : Wash out mouth with water. If victim has swallowed material and is still conscious give small amounts of water to drink. Stop if person feels sick. Do not induce vomiting unless directed to do so by medical personnel.. Seek immediate medical attention.

#### 4.2 Most important symptoms and effects, both acute and delayed.

- Eye contact : Causes serious eye irritation
- Inhalation : No known significant effects or critical hazards
- Skin contact : Causes skin irritation. May cause an allergic skin reaction
- Ingestion : Irritating to mouth, throat and stomach.

Over exposure signs/symptoms	
Eye contact	Adverse symptoms may include the following: Pain or irritation Watering Redness
Inhalation	No known significant effects or critical hazards
Skin contact	Adverse symptoms may include the following: Irritation Redness
Ingestion	No specific data

- 4.3 Indication of any immediate medical attention and special treatment needed  
No specific treatment

#### SECTION 5. Fire-fighting measures

- 5.1 Extinguishing media  
Suitable extinguishing media Use an extinguishing agent suitable for the surrounding fire.  
Unsuitable extinguishing media None known
- 5.2 Special hazards arising from the substance  
Hazards from the substance or mixture Incomplete combustion may form carbon dioxide ,carbon monoxide and halogenated compounds.
- 5.3 Advice for fire-fighters  
Special protective actions for fire fighters Promptly isolate the scene by removing all persons from the vicinity of the fire.  
Special protective equipment for fire fighters Fire fighters should wear appropriate protective equipment.

#### SECTION 6. Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures  
Wear suitable protective clothing, gloves and eye/face protection. Use self contained breathing apparatus and chemically protective clothing.
- 6.2 Environmental precautions  
Prevent contamination of soil and water.  
Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers.
- 6.3 Methods and material for containment and cleaning up  
Transfer to a labelled, sealable container for product recovery or safe disposal. Treat residues as for small spillage

#### SECTION 7. Handling and storage

- 7.1 Precautions for safe handling  
Protective measures Wear appropriate personal protective equipment. Avoid contact with eyes, skin or clothing. Do not ingest. Keep containers closed when not in use.  
Advice on general occupational hygiene Do not eat, drink or smoke when handling this product. Wash hands after handling.
- 7.2 Conditions for safe storage, including any incompatibilities  
Keep containers tightly closed in a dry, cool and well ventilated areas  
Do not store in unlabelled containers.

#### SECTION 8. Exposure controls/personal protection

- 8.1 Control parameters  
Occupational exposure limits No exposure limit value known
- 8.2 Exposure controls  
Provide readily accessible eye wash stations and safety showers. Provide natural or explosion proof ventilation adequate to ensure concentrations are kept below explosion limits.
- Personal protective equipment  
Hand protection Chemically resistant, impervious gloves should be worn at all times when handling.  
Butyl rubber, Nitrile rubber, neoprene gloves, impervious gloves, latex or vinyl disposable gloves.  
Eye/face protection Protective eye glasses or goggles must be worn.  
Skin and body protection Standard issue work clothes. Long sleeve shirts, trousers or overalls must be worn.  
Environmental exposure controls Construct a dike to prevent spreading.

#### SECTION 9. Physical and chemical properties

- 9.1 Information on basic physical and chemical properties  
Physical state/colour Wet sand  
Odour Not available  
Relative density Not available  
Flash Point 150°C  
Viscosity Not available  
Ph Not available

#### SECTION 10. Stability and reactivity

- 10.1 Reactivity Stable under normal conditions
- 10.2 Chemical stability This product is stable
- 10.3 Possibility of hazardous reactions No specific data
- 10.4 Conditions to avoid No specific data
- 10.5 Incompatible materials No specific data
- 10.6 Hazardous decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced

## SECTION 11. Toxicological information

11.1 Information on toxicological effects	
Acute Toxicity	
No data available on the product itself.	
Components - Oral	
Epoxy Resin Bisphenol Type A	No acutely toxic in rat and mouse studies, LD50>2000mg/kg
Formaldehyde, polymer with (chloromethyl) oxirane and phenol, Oxirane, mono{(C12-C14-alkyloxy methyl) derivs.	No acutely toxic in rat and mouse studies, LD50>2000mg/kg
	LD50 >2.0grams (Female Rat) and LD50 = 26.8 grams (Male Rat)
Components - Inhalation	
Epoxy Resin Bisphenol Type A	Due to the low vapour pressure, meaning ful acute inhalation studies could not be conducted.
Formaldehyde, polymer with (chloromethyl) oxirane and phenol, Oxirane, mono{(C12-C14-alkyloxy methyl) derivs.	No specific data
	No mortalities were observed in rats exposed for 7 hours to the saturated vapour (150mg/m <sup>3</sup> )
Components – Dermal	
Epoxy Resin Bisphenol Type A	No acutely toxic in rat and mouse studies, LD50>2000mg/kg
Formaldehyde, polymer with (chloromethyl) oxirane and phenol, Oxirane, mono{(C12-C14-alkyloxy methyl) derivs.	No specific data
	No specific data
Potential acute health effects	
Eye contact	Causes serious eye irritation.
Inhalation	Irritating to mouth, throat and stomach.
Ingestion	No known significant effects or critical hazards
Over exposure signs/symptoms	
Eye contact	Adverse symptoms may include the following: Pain or irritation Watering Redness
Inhalation	No known significant effects or critical hazards
Skin contact	Adverse symptoms may include the following: Irritation Redness
Ingestion	No specific data
Chronic toxicity or effects from long term exposures	
Carcinogenicity	No known significant effects or critical hazards
Reproductive toxicity	No known significant effects or critical hazards
Germ cell mutagenicity	No specific data is available.

## SECTION 12. Ecological information

12.1 Toxicity	
Aquatic toxicity	No data is available on the products itself
Epoxy Resin Bisphenol Type A	Acute LC50 1.30 mg/l Fish
Formaldehyde, polymer with (chloromethyl) oxirane and phenol, Oxirane, mono{(C12-C14-alkyloxy methyl) derivs.	Acute LC50 2.54 mg/l Fish
	Acute LC50 1.80 mg/l Fish – Rainbow Trout
	Acute EC50 844 mg/l Aquatic Plants - Algae
12.2 Persistence and degradability	No data available
12.3 Bioaccumulative potential	No data available
12.4 Mobility in soil	No data is available

## SECTION 13. Disposal considerations

13.1 Waste treatment methods	
Product	Waste to be treated as controlled waste. Dispose to licensed waste disposal site. In accordance with local waste disposal authority.
Packaging	Keep container labelled until cleaned and then remove or deface labels. Drain container thoroughly and rinse well with water. Treat rinsings as for product disposal. Empty packaging should be removed by a licensed waste contractor.

## SECTION 14 Transport information

14.1 UN Number	
14.2 UN Proper shipping name	
14.3 Transport Hazard Class	
14.4 Packaging Group	

### Land Transport ADR / ADN

UN Number	3082
UN Proper Shipping Name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S. ( LIQUID EPOXY RESIN, ALIPHATIC GLYCIDYL ETHER)

Transport Hazard Class 9  
Packaging Group 111

**Air Transport ICAO / IATA**

UN Number 3082  
UN Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID  
N.O.S. ( LIQUID EPOXY RESIN, ALIPHATIC GLYCIDYL ETHER)  
Transport Shipping Class 9  
Packaging Group 111

**Maritime Transport IMO / IMDG**

UN Number 3082  
UN Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID  
N.O.S. ( LIQUID EPOXY RESIN, ALIPHATIC GLYCIDYL ETHER)  
Transport Shipping Class 9  
Packaging Group 111

14.5 Environmental hazards  
Environmentally hazardous and/or marine pollutant : YES

**SECTION 15. Regulatory information**

15.1 Safety, health and environment regulations/legislation specific for the substance or mixture  
EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV – List of substances to authorisation.  
Substances of very high concern

Carcinogen : Not listed  
Mutagen : Not listed  
Toxic to reproduction : Not listed  
PBT : Not listed  
VPvB : Not listed

**SECTION 16. Other Information**

Hazard Statements

H315 Causes skin irritation  
H317 May cause an allergic skin reaction  
H319 Causes serious eye irritation  
H411 Toxic to aquatic life with long lasting effects

Full Text of Classifications (CLP)

Skin Corrosion/Irritation Category 2, H315 Skin Corrosion/irritation – Category 2  
Skin Sensitisation Category 1, H317 Skin Sensitisation - Category 1  
Eye Damage/Irritation Category 2, H319 Serious Eye Damage/Eye Irritation – Category 2  
Aquatic Chronic Category 2, H411 Aquatic Hazard (Long lasting) – Category 2

Date Issued : 20..01.2016  
Reference : EMUA/A/08  
Product Code : Epoxy Products Epoxy Mortar UA (Resin- Pack A)  
Intended Use : Epoxy resin mortar

The information is based on our current knowledge and is intended to describe the product for the purpose of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

# MATERIAL SAFETY DATA SHEET

## EPOXY MORTAR UA PACK B

### SECTION 1: Identification of the substance/mixture and of the company/undertaking.

- 1.1 Product identifier : Epoxy Products Epoxy Mortar UA - Pack B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against  
Use of the substance/mixture : Epoxy Curing Agent
- 1.3 Details of the supplier of the safety data sheet : Epoxy Products Limited, Unit 7 Haviland Road, Ferndown Industrial Estate, Wimborne, Dorset. BH21 7RZ England  
Tel No. +44 (0) 1202 891899
- Email Address – Technical Information : [sales@epoxyproducts.co.uk](mailto:sales@epoxyproducts.co.uk)
- Telephone : +44 (0) 1202 891899
- 1.4 Emergency telephone number : +44 (0) 1202 891899

### SECTION 2: Hazards Identification

- 2.1 Classification according to Regulation 1272/2008  
Repr. Category 2 H361f : Suspected of damaging fertility.  
Skin corrosion Category 1B: H314 : Causes severe skin burns and eye damage  
Eye damage Category 1: H318 : Causes serious eye damage.  
Skin Sens. Category 1: H317 May cause an allergic skin reaction

- 2.2 Label Elements  
Hazard pictograms/symbols



Signal Word: Danger

Hazard Statements:  
H314: Causes severe skin burns and eye damage  
H317: May cause an allergic skin reaction.  
H361f: Suspected of damaging fertility

Precautionary Statements:

- Prevention : P260: Do not breathe dust/fume/gas/mist/vapours/spray  
Response : P303+P361+P353 : IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310: Immediately call a POISON CENTRE/doctor.
- Disposal : P405: Store locked up.  
P501: Disposal of contents/container to be specified in accordance with national regulations.

- 2.3 Other Hazards  
Results of PBT and vPvB assessment : Both not applicable

### SECTION 3. Composition/Information on Ingredients

Substance/Mixture	: Mixture				
Component	EINECS	CAS Number	Concentration %	Classification (CLP)	REACH REG
Benzyl Alcohol	202-859-9	100-51-6	5 - 10	Acute Tox. Inha 4 ; H332 Acute Tox. Oral 4 ; H302 Eye Irrit. 2 : H319	01-2119492630-38-xxxx
3-aminomethyl-3,5,5- trimethyl cyclohexylamine	220-666-8	2855-13-2	<1	Skin Corr. 1B : H314 Acute Tox. Oral 4 ; H302 Acute Tox. Inhal 4; H312 Skins Sens. 1 : H317 Aquatic Chronic 3 : H412	01-2119514687-32-xxxx
M-phenylenebis(methylamine)	216-032-5	1477-55-0	<1	Skin Corr. 1B : H314 Acute Tox. Oral 4 ; H302 Acute Tox. Inhal 4; H332 Skins Sens. 1 : H317 Aquatic Chronic 3 : H412	01-2119480150-50-xxxx

### SECTION 4: First-aid measures

- 4.1 Description of first aid measures
- Eye Contact : Rinse immediately with plenty of water also under the eyelids for at least 20 minutes. Remove contact lenses.
- Skin Contact : Wash off immediately with plenty of water for at least 20 minutes. Wash off with soap and water. Immediately remove contaminated clothing and any extraneous chemical without delay.

Ingestion	Never give anything by mouth to an unconscious person. Prevent aspiration of vomit. Turn victims head to one side. Call doctor immediately.
Inhalation	Remove to fresh air. If rapid recovery does not occur, obtain medical attention.
4.2 Most important symptoms and effects, both acute and delayed.	
Symptoms	No data available
4.3 Indication of any immediate medical attention and special treatment needed	No data available

#### SECTION 5. Fire-fighting measures

5.1 Extinguishing media	Alcohol resistant foam, carbon dioxide, dry chemical, dry sand or limestone powder
Extinguishing media – Not suitable	No data available
5.2 Special hazards arising from the substance	Incomplete combustion may form carbon monoxide. May generate ammonia gas. May generate toxic oxide gases. Burning produces noxious and toxic fumes. Downwind personnel must be evacuated
5.3 Advice for fire-fighters	Avoid contact with skin. Use personal protective equipment. Wear self-contained breathing apparatus for fire fighting if necessary.

#### SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment	Wear suitable protective clothing, gloves and eye/face protection. Use self contained breathing
6.2 Environmental precautions	Prevent contamination of soil and water. Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers.
6.3 Methods and material for containment and cleaning up	Transfer to a labelled, sealable container for product recovery or safe disposal. Treat residues as for small spillage

#### SECTION 7. Handling and storage

7.1 Precautions for safe handling	Do not use sodium nitrate or other nitrosating agents in formulations containing this product. Suspected cancer causing nitrosamines could be formed. Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations. Avoid contact with eyes. Use personal protective equipment. When using, do not eat, drink or smoke.
7.2 Conditions for safe storage, including any incompatibilities	Do not store near acids. Keep away from alkalis. Keep containers tightly closed in a dry, cool and well ventilated place.

#### SECTION 8. Exposure controls/personal protection

8.1 Control parameters	If applicable, refer to the extended section of the MSDS (available upon request)
8.2 Exposure controls	Provide readily accessible eye wash stations and safety showers. Provide natural or explosion proof ventilation adequate to ensure concentrations are kept below explosion limits.
8.3 Personal protective equipment	
Hand protection	Chemically resistant, impervious gloves should be worn at all times when handling. Butyl rubber, Nitrile rubber, neoprene gloves, impervious gloves, latex or vinyl disposable gloves.
Eye/face protection	Protective eye glasses or goggles must be worn.
Skin and body protection	Standard issue work clothes. Long sleeve shirts, trousers or overalls must be worn.
Environmental exposure controls	Construct a dike to prevent spreading.
Special instructions for protection and	Discard contaminated clothing. Provide accessible eye wash stations and safety showers. Wash hands at the end of each workshift and before eating, drinking, smoking or using the toilet.

#### SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties	
Physical state/colour	Wet sand
Odour	Amine like
Relative density	2.00 g/m <sup>3</sup>
Self inflammability	Product is not self-igniting
Danger of explosion	Product is not explosive

#### SECTION 10. Stability and reactivity

10.1 Reactivity	Refer to possibility of hazardous reactions and/or incompatible materials section
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	No dangerous reactions known
10.4 Conditions to avoid	No data available
10.5 Incompatible materials	Amines Incompatible with bases Reducing agents Reactive materials, eg sodium calcium, zinc etc. Materials with hydroxyl compounds Oxidising agents.
10.6 Hazardous decomposition products	In the event of fire: Poisonous gases/vapours and/or corrosive gases/vapours

## SECTION 11. Toxicological information

### 11.1 Information on toxicological effects

Likely routes of exposure	
Effects on Eye	Causes eye burns
Effects on Skin	Causes skin burns
Ingestion Effects	Swallowing will lead to a caustic effect on the moth, throat and stomach
Acute Inhalation Toxicity	No data available on the product itself.
Acute Oral Toxicity	No data available on the product itself.
Acute Oral Toxicity - Components	
Benzyl Alcohol	LD50 : 1040mg/kg Species : Mouse and Rabbit LD50 : 1620mg/kg Species : Rat
Acute Dermal Toxicity	No data available on the product itself.
Acute Dermal Toxicity – Components	
Benzyl Alcohol	LD50: 2,000 mg/kg Species: Rabbit
Sensitisation	May cause sensitisation of susceptible persons by skin contact.
Chronic toxicity or effects from long term exposures	
Carcinogenicity	No data is available
Reproductive toxicity	No data is available on the product itself
Germ cell mutagenicity	No data is available on the product itself.
Specific target organ systemic toxicity (single exposure)	No data is available on the products itself
Specific target organ systemic toxicity (repeated exposure)	This product contains no listed carcinogens according to Directive 67/548/EEC, IARC, ACGIH and/or NTP in concentrations of 0.12 percent or greater..
Aspiration hazard	No data available

## SECTION 12. Ecological information

### 12.1 Toxicity

Aquatic toxicity	No data is available on the products itself
Toxicity to fish – Components	
Benzyl Alcohol	LC50 (96 h) : 460mg/l Species: Pimephales promelas
Toxicity to daphnia - Components	
Benzyl Alcohol	EC50 (24 h) : 400mg/l Species: Daphnia magna
Toxicity to algae – Components	
Benzyl Alcohol	EC50 (96 h) : 640 mg/l Species: Algae

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available on the product itself

#### Bioaccumulative – Components

Benzyl Alcohol Low bioaccumulation potential

### 12.4 Mobility in soil

No data is available

## SECTION 13. Disposal considerations

#### Waste treatment methods

Waste to be treated as controlled waste. Dispose to licensed waste disposal site. In accordance with local waste disposal authority.

#### Contaminated Packaging

Keep container labelled until cleaned and then remove or deface labels. Drain container thoroughly and rinse well with water. Treat rinsings as for product disposal. Empty packaging should be removed by a licensed waste contractor.

## SECTION 14 Transport information

### 14.5 UN Number

### 14.6 UN Proper shipping name

### 14.7 Transport Hazard Class

### 14.8 Packaging Group

#### Land Transport ADR

UN Number	2735
UN Proper Shipping Name	2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))
Transport Hazard Class	8
Packaging Group	111

#### Air Transport ICAO / IATA

UN Number	2735
UN Proper Shipping Name	2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))
Transport Shipping Class	8
Packaging Group	111

#### Maritime Transport IMO / IMDG

UN Number	2735
UN Proper Shipping Name	2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))
Transport Shipping Class	8
Packaging Group	111

## SECTION 15. Regulatory information

15.1 Safety, health and environment regulations/legislation specific for the substance or mixture  
Country : EU  
Regulatory List : EINECS  
Notofication : Included on EINECS inventory

## SECTION 16. Other Information

### Hazard Statements

H302: Harmful if swallowed  
HH314: Causes sever skin burns and eye damage  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation  
H332: Harmful if inhaled  
H361f: Suspect of damaging fertility  
H412: Harmful to aquatic life with long lasting effects.

Date Issued : 20.01.2016  
Reference : EMUA/B/08  
Product Code : Epoxy Products Epoxy Mortar UA (Hardener - Pack B)  
Intended Use : Epoxy resin mortar

The information is based on our current knowledge and is intended to describe the product for the purpose of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.