



*Manufacturers of High
Performance Floor
Coatings and
Re-Surfacing Screeds*

**S
C
R
E
E
D
S**

Epoxy Products Limited
7 Haviland Road
Ferndown Industrial Estate
Wimborne
Dorset
BH21 7RZ

Phone: 01202 891899
Fax: 01202 896983
Email: sales@epoxyproducts.co.uk
Web: www.epoxyproducts.co.uk

Epoxy Screed Water Based

- ▲ **Outstanding Early Strength**
- ▲ **Non-Porous, Good Slip Resistance**
- ▲ **Solvent Free - Virtually Odourless**
- ▲ **Excellent Chemical Resistance**



THE RANGE

We have been manufacturing a range of concrete repair and resurfacing products for over three decades. All offer outstanding strength, wear resistance, chemical resistance, impact resistance and long term performance. For resurfacing damaged or worn concrete.

EPOXY SCREED HEAVY DUTY

Developed to provide an exceptionally tough thin floor resurfacing screed for concrete floors that need protection from fork trucks, heavy industrial use and chemical spillage. The rapid high strength development enables early return to use.

It is available in 10kilo and 20kilo packs

<http://www.epoxyproducts.co.uk/screed.html>

Epoxy Screed Water Based



Manufacturers of High
Performance Floor
Coatings and
Re-Surfacing Screeds

SCREEDS

Epoxy Products Limited
7 Haviland Road
Ferndown Industrial Estate
Wimborne
Dorset
BH21 7RZ

Phone: 01202 891899
Fax: 01202 896983

Email: sales@epoxyproducts.co.uk
Web: www.epoxyproducts.co.uk

DESCRIPTION

EPOXY SCREED WATER BASED is a three part, solvent free epoxy resin, formulated to provide a thin resurfacing screed for concrete floors. This non-porous, slip resistant, easy to clean finish is ideal for areas that demand a tough hard wearing and decorative surface.

USES: Thin industrial floor topping screeds in dairies, bakeries, breweries, food preparation areas, engineering shops, chemical stores, kitchens, sports changing rooms and all other areas that demand a hygienic and durable permanent surface.

PREPARATION: Surfaces can be dry or damp but free from grease, oil and other forms of contamination. Remove any loose materials and sweep clean. Cleaning is imperative. For large areas vacuum shot blasting is recommended. For small areas ensure the concrete is clean and sound. For chemical cleaning use our CONCRETE CLEANER.

CONCRETE REPAIRS: Fill deep holes and badly worn concrete prior to priming with Patching Mortar or Epoxy Filler. Allow expansion joints to follow through the new floor.

CONCRETE TEMPERATURE: Ensure the concrete temperature to be resurfaced is constantly above 10°C during the application and throughout the hardening period.

PRIMING: The concrete must be primed with EPOXY SEALER WB the day prior to applying the EPOXY SCREED HD. For small areas use TACK PRIMER WB immediately prior to laying. Working across the floor in strips lay on top of the Tack Primer while it is wet.

MIXING: Empty the contents of Pack "B" (Hardener) into Pack "A" (Resin) and mix thoroughly together by hand. Pour the mixed Resin/Hardener into the large bucket containing Pack "C" (Filler) and stir using either:- for large quantities use a "Forced Action Mixer" or for smaller quantities an electric drill and paddle attachment. Continue to mix until uniform in colour for at least 3 minutes.

APPLICATION: Pour the mixed material onto the primed floor. Apply immediately using a steel trowel to the required depth, normally between 3mm and 6mm. Occasionally clean the face of the trowel using WATER to release the build up of resin tack.

HEALTH & SAFETY: Read the Health & Safety Data Sheet prior to handling this product.

PRODUCT DATA

COVERAGE

10kg should cover 1m² at 5mm depth depending upon the texture of the concrete

POT LIFE

When fully mixed, approximately 25-30 minutes @ 20°C. Extended pot life at lower temperatures. Reduced period at high temperatures.

CURING TIME

Light traffic after 24 hours @ 20°C. Suitable for fork trucks after 48 hours @ 20°C. Full cure, strength and chemical resistance after 7 days.

CHEMICAL RESISTANCE

Resistant to spillages of many chemicals commonly met within industry.

Contact Technical Services for more advice.

STRENGTH	AFTER 24 HOURS	3 DAYS	7 DAYS
Tensile Strength	10.00 MN/m ²	17.00 MN/m ²	23.00 MN/m ²
Compressive Strength	31.86 MN/m ²	48.00 MN/m ²	90.00 MN/m ²
Flexural Strength	-	16.00 MN/m ²	20.00 MN/m ²

TOOL CLEANING

Clean all tools with WATER and detergent.

COLOURS

Available in a range of colours. Colour matching service available.

PACK SIZE

Available in 10kg and 20kg packs. Combined weight of Resin, Hardener and Filler

SHELF LIFE:

12 Months in sealed containers stored under normal conditions

Whilst Epoxy Products Limited endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it can not, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification or information given.