

Floor Paint Water Based



*Manufacturers of High
Performance Floor
Coatings and
Re-Surfacing Screeds*

COATINGS

- ▲ **Dustproofs Concrete**
- ▲ **Easy to use, applied by brush or roller**
- ▲ **Water Based Dispersion**
- ▲ **Tough Durable Satin Finish**



EPOXY PRODUCTS FLOOR PAINT WB is a single pack, quick drying, non toxic water based acrylic dispersion, designed to seal, colour and protect concrete floors. This tough, durable paint will transform drab looking concrete floors into an area that looks clean, hygienic and dustfree.

EPOXY PRODUCTS FLOOR PAINT WB offers excellent water, petrol and oil resistance. It also offers excellent colour retention and long lasting durability.

EPOXY PRODUCTS FLOOR PAINT WB is easy to apply directly from the container. The rapid drying will enable quick and simple applications with minimum disruption.

Available in 5 Litre and 20 Litre tins.

Epoxy Products Limited
7 Haviland Road
Femdown Industrial Estate
Wimborne
Dorset
BH21 7RZ

Phone: 01202 891899
Fax: 01202 896983
Email: sales@epoxyproducts.co.uk
Web: www.epoxyproducts.co.uk



Manufacturers of High
Performance Floor
Coatings and
Re-Surfacing Screeds

COATINGS

Epoxy Products Limited
7 Haviland Road
Ferndown Industrial Estate
Wimborne
Dorset
BH21 7RZ

Phone: 01202 891899
Fax: 01202 896983
Email: sales@epoxyproducts.co.uk
Web: www.epoxyproducts.co.uk

Floor Paint WB

DESCRIPTION

EPOXY PRODUCTS FLOOR PAINT WB is a quick drying non toxic single pack water based acrylic paint designed to seal, colour and protect concrete and wooden floors. Excellent water, petrol and oil resistant. Excellent long lasting durability and colour retention. It is non toxic, odourless, inexpensive and easy to apply.

USES: Treatment of industrial floors that require to be dustproof and easy to clean. Ideally suitable for workshops, garages and most environments that require high levels of decorative appearance and long lasting performance.

PREPARATION: Surfaces must be clean, sound, dry and free from grease, oil and other forms of contamination. Concrete laitence should be removed by acid washing using EPOXY PRODUCTS CONCRETE ETCH and rinsed thoroughly. All surfaces to be painted must be sound and dry. This paint can be applied onto previously painted floors. New concrete floors can only be painted after 6—8 weeks.

MIXING: This product is supplied ready for use directly from the tin. Stir the tin before use.

APPLICATION: Apply by brush or roller to obtain a thin even application. Use a small brush to paint around the perimeter wall, this will prevent the large paint roller from hitting the walls. Apply to the remaining area using a large paint roller and tray. Two thin applications are normally required. On porous concrete floors dilute the first coat with 10% cold water. Allow the first coat to become “touch dry” and apply the second coat within 24 hours of the first.

HEALTH AND SAFETY: It is important that prior to handling this product the “Health & Safety Data Sheet” must be read and understood. Always wear personal protective clothing as recommended when handling this product.

PRODUCT DATA

COLOURS Red (04C39) Green (14C39) Light Grey (00A05) and Black

APPEARANCE Satin, semi gloss finish

VOLUME SOLIDS 50%

DRY TO TOUCH 2 - 4 hours @ 20°C with ventilation/air movement

OVER COATING TIME 8 - 10 hours

THEORETICAL SPREADING RATE
10- 12 square metres per litre depending upon the porosity and texture of the substrate.

SPECIFIC GRAVITY 1.20

THINNERS Water

LIMITATIONS Do not use in temperatures below 10°C

TOOL CLEANING Clean all tools with cold water.

SHELF LIFE
12 months in sealed containers. Protect from frost. Store in cool dry conditions above 10° C.

PACKAGING
5 Litre and 20 Litre tins

Whilst Epoxy Products Limited endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it can not, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification or information given.