

Industrial Floor Paint



*UK Manufacturers of
High Performance
Floor Coatings and
Re-Surfacing Screeds*

COATINGS

- ▲ **Transforms Drab, Stained Concrete**
- ▲ **Easy to Clean**
- ▲ **Inexpensive**
- ▲ **Easy to Apply—Single Pack**



EPOXY PRODUCTS INDUSTRIAL FLOOR PAINT is an attractive, hard wearing, inexpensive floor paint for concrete floors available in a wide range of colours

EPOXY PRODUCTS INDUSTRIAL FLOOR PAINT will transform and upgrade drab, dusty stained concrete floor areas into highly decorative areas—inexpensively to!

EPOXY PRODUCTS INDUSTRIAL FLOOR PAINT is ideal for colour designation of production areas, warehouse and storage facilities and trafficked gangways.

Available in 5 litre and 25 litre packs.

Epoxy Products Limited
Unit 7 Haviland Road
Ferndown Ind. Estate
Wimborne
Dorset
BH21 7RZ

Phone: 01202 891899
Fax: 01202 896983

Email: sales@epoxyproducts.co.uk
Web: www.epoxyproducts.co.uk

Industrial Floor Paint



UK Manufacturers of
High Performance
Floor Coatings and
Re-Surfacing Screeds

COATINGS

Epoxy Products Limited
Unit 7 Haviland Road
Ferdown Ind. Estate
Wimborne
Dorset
BH21 7RZ

Phone: 01202 891899
Fax: 01202 896983

Email: sales@epoxyproducts.co.uk
Web: www.epoxyproducts.co.uk

DESCRIPTION

EPOXY PRODUCTS INDUSTRIAL FLOOR PAINT formulated single part urethane resin based system. It offers good resistance to oil and grease and spillages to a range of chemicals used within industry. It provides a hardwearing surface for interior applications.

USES: It will provide protection to a wide range of industrial floors and is ideally suitable for Warehouses, Workshops, Plant Rooms, Goods In/Out areas, in fact any floor that is trafficked by fork lift trucks, pallet trucks and pedestrians.

PREPARATION: Surfaces must be clean, dry, sound and free from grease, oil and other forms of contamination. Concrete laitance should be removed by acid washing using EPOXY PRODUCTS CONCRETE ETCH and rinsed thoroughly. For best results Vacuum Track Shot Blasting is recommended. This coating may also be applied onto previously painted floors providing the existing floor paint is sound and well abraded.

MIXING: Simply stir well before use. Add 10% White Spirit for the first priming coat.

APPLICATION: Apply the coating by brush or roller. Two coats are normally required for maximum resistance. For best results apply the second application within 24 hours of the first. Anti-slip aggregates can be applied to the floor paint to provide some slip resistance particularly in wet areas.

HEALTH AND SAFETY: As some people find Epoxy based products irritant to the skin, all users are recommended to use barrier cream and thoroughly wash with soap and water after use. Avoid skin and eye contact. If eye contact is made then rinse with clean water and seek immediate medical advice.

PRODUCT DATA

COVERAGE

5 Litres will cover up to 50 square metres depending upon the porosity and texture of the substrate.

HARDENING TIME

Tack free in 8 hours @ 20⁰ C. Re-coatable in 12 hours @ 20⁰ C. Full hardness in 7 days.

CHEMICAL RESISTANCE

Limited resistance to spillages of chemicals commonly met within industry. Seek Technical advice from EPOXY PRODUCTS TECHNICAL DEPARTMENT.

TOOL CLEANING

Clean all tools with White Spirit.

COLOUR RANGE

Slate Grey, Frigate Grey, Silver Grey, Red, British Racing Green, Buff and Blue

Whilst Epoxy Products Limited endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it can not, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification or information given.